

Claro OA3 Outdoor LED Display Solution creates an exclusive experience by using its real color and clear image technology with high resolution.


Claro OA3's durable structure and excellent wide-angle guarantee that its high performance is ensured without any decline in giving its high quality even if there are fierce weather conditions. Therefore, always live the exclusive difference of delivering your message at the highest quality

thanks to Claro OA3's high resolution.

## **FEATURES**

## **VIEWING DISTANCE & ANGLES**

- ⊲ Rear Maintenance Access
- ⊲ High Resolution
- ⊲ High Refresh Speed
- ⊲ Wide Viewing Angle
- ⊲ 2 Year Warranty
- ⊲ IP65-IP54 Rating
- Custom Production at Demanded Dimensions



















## SPECS

ENVIRONMENT	OUTDOOR
MODEL	OA3
PIXEL PITCH (mm)	3,07
PIXEL DENSITY (Pixel/m²)	105625
PIXEL TYPE 1	1R1G1B
LED TYPE	SMD1515
MODULE SIZE (mm)	320x160
MODULE RESOLUTION (Pixel)	104x52
PANEL SIZE (mm)	960x960
PANEL RESOLUTION (Pixel)	312x312
DISPLAY COLORS 2	281 Trillion
COLOR TEMPERATURE 2	2000-10000K Adjustable
CONTRAST RATIO	6000:1
VIEWING ANGLE	140°(Y)/ 140°(D)
VOLTAGE	220/110V AC
CABINET WEIGHT (kg)	42,4
MAX. POWER CONSUMPTION	≤785
AVARAGE POWER CONSUMPTION	≤262
BRIGHTNESS (CD/m²)	≥5000
REFRESH RATE 3	3840 Hz
SCAN RATE 1	1/13
IP RATING	IP65-IP54
OPERATING TEMPERATURE/ OPERATING HUMIDITY -	-20oC-+50oC; 10-90%
LIFE SPAN 1	100,000 Hours
QUALITY CERTIFICATES	CE

<sup>\*</sup>Performance specifications are typical. Due to constant research, specifications are subject to change without notice.