


Claro OA4 Outdoor LED Display Solution creates an exclusive experience by using its real color and clear image technology.

Claro OA4's durable structure and excellent wide-angle guarantee that its high performance is ensured without any decline in giving its high quality even if there are fierce weather conditions. Therefore, always live the exclusive difference of delivering your message at the highest quality thanks to Claro OA4's high resolution.

FEATURES

VIEWING DISTANCE & ANGLES

- ⊲ Rear Maintenance Access
- ⊲ High Resolution
- ⊲ High Refresh Speed
- ⊲ Wide Viewing Angle
- ⊲ 2 Year Warranty
- ⊲ IP65 / IP54 Certificate
- Custom Production at Demanded Dimensions



















SPECS

ENVIRONMENT OUTDOOR MODEL OA4 PIXEL PITCH (mm) 4 PIXEL DENSITY (Pixel/m²) 62500 PIXEL TYPE 1R1G1B LED TYPE SMD2525 MODULE SIZE (mm) 320x160 MODULE RESOLUTION (Pixel) 80x40
PIXEL PITCH (mm) 4 PIXEL DENSITY (Pixel/m²) 62500 PIXEL TYPE 1R1G1B LED TYPE SMD2525 MODULE SIZE (mm) 320x160
PIXEL DENSITY (Pixel/m²) 62500 PIXEL TYPE 1R1G1B LED TYPE SMD2525 MODULE SIZE (mm) 320x160
PIXEL TYPE 1R1G1B LED TYPE SMD2525 MODULE SIZE (mm) 320x160
LED TYPE SMD2525 MODULE SIZE (mm) 320x160
MODULE SIZE (mm) 320x160
MODILI E RESOLUTION (Pixel) 80v40
MODEL RESCENTION (LINE)
PANEL SIZE (mm) 960x960
PANEL RESOLUTION (Pixel) 240x240
DISPLAY COLORS 4398 Billion
COLOR TEMPERATURE 2000-10000K Adjustable
CONTRAST RATIO 7000:1
VIEWING ANGLE 140° (W)/ 140° (H)
VOLTAGE 220/110V AC
CABINET WEIGHT (kg) 44,2
MAX. POWER CONSUMPTION ≤822
AVARAGE POWER CONSUMPTION ≤279
BRIGHTNESS (CD/m²) ≥5500
REFRESH RATE 1920 Hz
SCAN RATE 1/10
IP RATING IP65-IP54
OPERATING TEMPERATURE/ OPERATING HUMIDITY -20oC-+50oC; 10-90%
LIFE SPAN 100,000 Hours
QUALITY CERTIFICATES CE

^{*}Performance specifications are typical. Due to constant research, specifications are subject to change without notice.