


Apart from its being ergonomically quite useful, Claro OA5 Outdoor LED Display Solution never fails to perform its superior quality.

You can use Claro OA5 Outdoor LED Display Solution with confidence at any time during the day in any weather condition. Thanks to Claro OA5, you can be ensured that, your message will be delivered to the expected place with the highest quality in any condition.

## **FEATURES**

## **VIEWING DISTANCE & ANGLES**

- ⊲ Rear Maintenance Access
- ⊲ High Resolution
- ⊲ High Refresh Speed
- ⊲ Wide Viewing Angle
- ⊲ 2 Year Warranty
- ⊲ IP65 / IP54 Certificate
- Custom Production at Demanded Dimensions



















## SPECS

ENVIRONMENT	OUTDOOR
MODEL	OA5
PIXEL PITCH (mm)	5
PIXEL DENSITY (Pixel/m²)	40000
PIXEL TYPE	1R1G1B
LED TYPE	SMD2525
MODULE SIZE (mm)	320x160
MODULE RESOLUTION (Pixel)	64x32
DISPLAY COLORS	4398 Billion
COLOR TEMPERATURE	2000-10000K Adjustable
CONTRAST RATIO	6000:1
VIEWING ANGLE	140° (W)/ 140° (H)
VOLTAGE	220/110V AC
MAX. POWER CONSUMPTION	≤791
AVARAGE POWER CONSUMPTION	≤296
BRIGHTNESS (CD/m²)	≥5500
REFRESH RATE	1920 Hz
SCAN RATE	1/8
IP RATING	IP65-IP54
OPERATING TEMPERATURE/ OPERATING HUMIDITY	-20oC-+50oC; 10-90%
LIFE SPAN	100,000 Hours
QUALITY CERTIFICATES	CE

 $<sup>{}^\</sup>star \text{Performance specifications are typical. Due to constant research, specifications are subject to change without notice.}$ 

