


Thanks to the real and flawless image quality of Claro SG2 Indoor LED Display Solution, which is suitable for cinemas, airports, shops and any utilization areas that you can imagine, you won't be able to get your eyes from that.

Therefore, live the privilige of delivering your message you want with Claro SG2 model in the dimension and color you want and without losing any quality.

FEATURES

VIEWING DISTANCE & ANGLES

- ⊲ Front & Rear Maintenance Access
- ⊲ High Resolution
- ⊲ High Refresh Speed
- ⊲ Wide Viewing Angle
- ⊲ 2 Year Warranty
- □ Custom Production at Demanded Dimensions

















SPECS

<u> </u>	
ENVIRONMENT	INDOOR
MODEL	SG2
PIXEL PITCH (mm)	2
PIXEL DENSITY (Pixel/m²)	250000
PIXEL TYPE	1R1G1B
LED TYPE	SMD1515
MODULE SIZE (mm)	320x160
MODULE RESOLUTION (Pixel)	160x80
PANEL SIZE (mm)	640x480
PANEL RESOLUTION (Pixel)	320x240
DISPLAY COLORS	281 Trillion
COLOR TEMPERATURE	2000-13000K Adjustable
CONTRAST RATIO	5000:1
VIEWING ANGLE	140° (W)/ 140° (H)
VOLTAGE	220/110V AC
CABINET WEIGHT (kg)	10,57
MAX. POWER CONSUMPTION	≤439
AVARAGE POWER CONSUMPTION	≤147
BRIGHTNESS (CD/m²)	800~1200
REFRESH RATE	3840 Hz
SCAN RATE	1/20
IP RATING	IP31
OPERATING TEMPERATURE/ OPERATING HUMIDITY	-0oC-+45oC; 10-90%
LIFE SPAN	100,000 Hours
QUALITY CERTIFICATES	CE

^{*}Performance specifications are typical. Due to constant research, specifications are subject to change without notice.