CLARO



Claro SM1.2 Indoor LED Screen Solutions, which is suitable for cinemas, controlling room, TV studios, conference halls, airports, meeting rooms, shops and every utilization area that you can imagine, provide you to deliver your message you want in its remarkable brightness and flawless image quality.

SM1.2 model brings all the qualifications that you would expect from a LED screen, to your use by providing you to deliver your message in any aspect and any color without losing any quality.

1600.

FEATURES

VIEWING DISTANCE & ANGLES

- Front & Rear Maintenance Access
- ⊲ High Resolution
- High Refresh Speed
- ⊲ Wide Viewing Angle
- ⊲ 2 Year Warranty
- Custom Production at Demanded Dimensions



SPECS

ENVIRONMENT	FINE PITCH
MODEL	SM1.2
PIXEL PITCH (mm)	1,25
PIXEL DENSITY (Pixel/m²)	640000
PIXEL TYPE	1R1G1B
LED TYPE	SMD1010
MODULE SIZE (mm)	320x160
MODULE RESOLUTION (Pixel)	256x128
PANEL SIZE (mm)	640x480
PANEL RESOLUTION (Pixel)	512x384
DISPLAY COLORS	281 Trillion
COLOR TEMPERATURE	2000-13000K Adjustable
CONTRAST RATIO	5000:1
VIEWING ANGLE	160°(W)/ 160°(H)
VOLTAGE	220/110V AC
CABINET WEIGHT (kg)	10,57
MAX. POWER CONSUMPTION	≤703
AVARAGE POWER CONSUMPTION	≤350
BRIGHTNESS (CD/m ²)	800~1200
REFRESH RATE	3840 Hz
SCAN RATE	1/32
IP RATING	IP31
OPERATING TEMPERATURE/ OPERATING HUMIDITY	-0oC-+45oC; 10-90%
LIFE SPAN	100,000 Hours
QUALITY CERTIFICATES	CE

*Performance specifications are typical. Due to constant research, specifications are subject to change without notice.