


Claro SM1.5 Indoor LED Display Solution provides you to make a difference by using real color and sharp image technology.

The durable structure and wide angle of Claro SM1.5 guarantee to give high performance in every condition without any damage or decreasing any quality. Claro SM1.5 always succeeds to draw attention with its high resolution.

FEATURES

VIEWING DISTANCE & ANGLES

- ⊲ Front & Rear Maintenance Access
- ⊲ High Resolution
- ⊲ High Refresh Speed
- ⊲ Wide Viewing Angle
- ⊲ 2 Year Warranty
- □ Custom Production at Demanded Dimensions

















SPECS

ENVIRONMENT	FINE PITCH
MODEL	SM1.53
PIXEL PITCH (mm)	1.53
PIXEL DENSITY (Pixel/m²)	422500
PIXEL TYPE	1R1G1B
LED TYPE	SMD1212
MODULE SIZE (mm)	320x160
MODULE RESOLUTION (Pixel)	208x104
PANEL SIZE (mm)	640x480
PANEL RESOLUTION (Pixel)	416x312
DISPLAY COLORS	281 Trillion
COLOR TEMPERATURE	2000-13000K Adjustable
CONTRAST RATIO	5000:1
VIEWING ANGLE	160° (W)/ 160° (H)
VOLTAGE	220/110V AC
CABINET WEIGHT (kg)	10,63
MAX. POWER CONSUMPTION	≤573
AVARAGE POWER CONSUMPTION	≤193
BRIGHTNESS (CD/m²)	800~1200
REFRESH RATE	3840 Hz
SCAN RATE	1/26
IP RATING	IP31
OPERATING TEMPERATURE/ OPERATING HUMIDITY	-0oC-+45oC; 10-90%
LIFE SPAN	100,000 Hours
QUALITY CERTIFICATES	CE

^{*}Performance specifications are typical. Due to constant research, specifications are subject to change without notice.